




OPTIMAX-ROTO Compact Air Handling Units

OPTIMAX-ROTO is a range of **energy efficient compact air handling units** that incorporating the latest thermal and ventilation technology. The units consist of a base section, a water or DX cooling coil section, and a section for sound attenuators. **The high-efficiency rotary** heat exchanger enables heat energy to be recovered from the extract air with up to **90% efficiency**. Additionally, the **high-efficiency fans with EC** motors are used to minimise power consumption. The double-skin panels are **50mm** thick and insulated with **mineral wool** to reduce heat loss to the environment. They also provide excellent acoustic insulation for the working fans. The **OPTIMAX-CROSS** air handling units come **fully pre-wired** with a built-in, pre-configured control panel installed in a basic section. Additionally, air shut-off dampers are fitted inside the basic section to the intake and discharge.

OPTIMAX-ROTO-30-M

DIMENSIONS



Dimensions

B [mm]	HB [mm]	LB [mm]	BW [mm]	HW [mm]	LC [mm]	LF [mm]	HP [mm]	LT [mm]	LBM* [mm]
1500	1500	2200	1400	650	600	800	100	800	2250

LBM* refers to the base section with mixing chamber. All dimensions are in [mm].

The standard version of the AHU can be modified in terms of the materials used after consultation with our technical department.

The extent of the modifications must be approved at the quotation stage.